


D7



Features:

- A slim directional profile height of 15mm.
- Directional angle ideal for indirect lighting, controlled and optimum illumination on objects.
- High quality extruded aluminium profiles.
- Frosted lens for uniform and smooth illumination.
- Dot free, continuous homogeneous lighting effect.
- 50mm incremental length continuous runs.
- Remote 24V driver, single driver for multiple lengths, cost effective solution.
- Life: 50,000 hours L90/B10.
- Easy to install with mounting brackets.

ITEM CODE	WATTAGE	COLOR TEMP	MIN LMD	LED IM
152210	10W	2700K	1000 X 15 X 15	680LM/M
152310	10W	3000K	1000 X 15 X 15	750LM/M
152410	10W	4000K	1000 X 15 X 15	800LM/M

Materials

Extruded aluminium profiles with high quality durable UV stabilized diffuser.



Applications

Cove lighting, cabinet lighting, display lighting, joinery lighting accent lighting and indirect lighting.

Options

- Dimming: DALI and DSI dimming
1-10V dimming
- CRI 95+
- Color Temperatures : 2700K, 3000K, 4000K, 5000K and 6000K
- Individual luminaire or continuous runs
- Customised wattages
- RGB LED boards
- Emergency modules

Accessories

