



Edge

LITENET presents a low glare range of recessed light fittings for indoor architectural lighting application. There are two types of recessed mounted light fittings a fitting with minimum Trim and there is also a Trim less version to maximise dark light effect. The Edge range of fixtures are constructed with premium grade aluminium for rapid heat dissipation.

The Edge is all about providing comfortable lighting to create a functional space, whether it's a commercial fitout or a residential living space. The Edge range recessed light fittings adds style and elegance.

This is an architectural fitting which is designed for low glare maximum effective light output with minimal trim and optimum lighting control.

The Edge range is available in CW and WW

LITENET will supply a 50,000 hour 5-year warranty



Edge 2



Edge 4



Edge 10



Edge 20



Edge 30





Edge 2

Power	2W	2W
Luminous flux	152lm	170lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge2-23-CBW-82	Edge2-24-CBW-82
Dimensions	45x45x49 mm	
Cut out	37x37 mm	

Edge 4

Power	4W	4W
Luminous flux	304lm	340lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge4-43-CBW-82	Edge4-44-CBW-82
Dimensions	75x45x49 mm	
Cut out	68x37 mm	

Edge 10

Power	10W	10W
Luminous flux	760lm	850lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge10-103-CBW-82	Edge10-104-CBW-82
Dimensions	147x45x49 mm	
Cut out	37x37 mm	





Edge 20

Power	20W	20W
Luminous flux	1520lm	1700lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge20-203-CBW-82	Edge20-204-CBW-82
Dimensions	280x45x49 mm	
Cut out	273x37 mm	



Edge 30

Power	30W	30W
Luminous flux	2280lm	2550lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge30-303-CBW-82	Edge30-304-CBW-82
Dimensions	415x45x49 mm	
Cut out	405x37 mm	

Edge TRIMLESS



Edge 2 TL

Power	2W	2W
Luminous flux	152lm	170lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge2TL-23-CBW-82	Edge2TL-24-CBW-82
Dimensions	38x71x49 mm	
Cut out	42x41 mm	



Edge 4 TL

Power	4W	4W
Luminous flux	304lm	340lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge4TL-43-CBW-82	Edge4TL-44-CBW-82
Dimensions	68x71x49 mm	
Cut out	72x41 mm	

Edge TRIMLESS



Edge 10 TL

Power	10W	10W
Luminous flux	760lm	850lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge10TL-103-CBW-82	Edge10TL-104-CBW-82
Dimensions	142x71x49 mm	
Cut out	145x41 mm	



Edge 20 TL

Power	20W	20W
Luminous flux	1520lm	1700lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge20TL-203-CBW-82	Edge20TL-204-CBW-82
Dimensions	274x71x49 mm	
Cut out	277x41 mm	

Edge TRIMLESS



Edge 30 TL

Power	30W	30W
Luminous flux	2280lm	2550lm
CCT	3000K	4000K
Input Voltage	AC 220-240V	AC 220-240V
Beam angles	15°,30°,45°	
CRI	80	80
Part No.	Edge30TL-303-CBW-82	Edge30TL-304-CBW-82
Dimensions	407x71x49 mm	
Cut out	410x41 mm	