

LITENET

Elite I



Product information



Source Type	LED Array
Corrected Colour Temperature	Specify 3000K or 4000K
Control gear	Electronic Driver
Cut out size	100mm x 100mm 93mm x 93mm x 103mm
IP	IP20
Power	10W
CRI	specify 80 or 90
Beam angle	24°, 36°

The Elite range of adjustable recessed downlights are elegantly designed for accent lighting. This range is designed with 30deg tilt and 360 rotatable gimble.

The heat sink and the trim is constructed with high grade aluminium to improve heat dissipation. The Elite range of adjustable down lights are designed with for low glare commercial lighting applications.

The Elite range of recessed twin adjustable down light finished are available in satin white or matte black.

Luminous flux at 25°C 3000K 860lm / 4000K 946lm

Colour Rendering Index specify >80 standard or >90 on request

CREE LED Chip with 3- Step Mac-Adam Ellipse

Non-dimmable ECG standard, Phase Dim/DALI is optional

50,000-hour 5 year warranty

Specification of the product

Beam angle	3000K CRI 80	4000K CRI 80	Beam Angle	3000K CRI 90
24°	LN-TGS-10.803.24	LN-TGS-10.804.24	24°	LN-TGS-10.903.24
36°	LN-TGS-10.803.38	LN-TGS-10.804.38	36°	LN-TGS-10.903.38