

ICON Q145

ICON QS145




ICON Q

LITENET presents a beautifully designed surface mounted, suspended square light fitting for commercial applications. The ICON Q range of surface mounted down lights are designed to create a living experience. To maximise heat dissipation the ICON Q is constructed with premium grade aluminium. This surface mounted down light is created with anti glare properties which includes black trim and a deep set aluminium reflector and clear glass diffuser. This surface mounted down light is powder coated in white finish.

The S Lite Kinetix is an architectural range of fittings which is designed and constructed to suit the indoor environment which accentuates comfort and low glare. The ICON Q is available in Black or white finish.

Non-dimmable driver is standard DALI dim is available

50,000-hour 5-year warranty



ICON Q145

ICON QS145

	15W	20W	25W	15W	20W	25W
Power	15W	20W	25W	15W	20W	25W
LED	COB	COB	COB	COB	COB	COB
Output current	350mA	450mA	550mA	350mA	450mA	550mA
CCT	3000K / 4000K	3000K / 4000K	3000K / 4000K	3000K / 4000K	3000K / 4000K	3000K / 4000K
Luminous flux	225lm	247lm	247lm	375lm	413lm	413lm
Dimensions (D x H)mm	100x100x145mm	100x100x145mm	100x100x145mm	100x100x150mm	100x100x150mm	100x100x150mm
Beam angle	15°, 25°, 38°, 60°	15°, 25°, 38°, 60°	15°, 25°, 38°, 60°	15°, 25°, 38°, 60°	15°, 25°, 38°, 60°	15°, 25°, 38°, 60°
CRI	80	80	80	80	80	80
Part No 3000K	ICON Q145 15-CW-83	ICON Q145 20-CW-83	ICON Q145 25-CW-83	ICON QS145 15-CW-83	ICON QS145 20-CW-83	ICON QS145 25-CW-83
Part No 4000K	ICON Q145 15-CW-84	ICON Q145 20-CW-84	ICON Q145 25-CW-84	ICON QS145 15-CW-84	ICON QS145 20-CW-84	ICON QS145 25-CW-84