



S18



ITEM CODE	WATTAGE	COLOR TEMP	DIM. (MM)	LED IM
181303	3W	3000K	150X18X8	210LM
181305	5W	3000K	300X18X8	350LM
181309	9W	3000K	600X18X8	630LM
181314	14W	3000K	900X18X8	980LM
181315	15W	3000K	1000X18X8	1050LM



Materials

Extruded aluminium profiles with durable UV stabilized diffuser.



Applications

Cabinet lighting, joinery, wardrobes, show cases, patios, coves, small niches, pelmet and indirect lighting.


Options

- **Dimming:** DALI and DSI dimming 1-10V dimming
- **Integrate motion sensor**
- **Color Temperatures :** 2700K, 3000K, 4000K, 5000K and 6000K
- **Individual luminaire or continuous runs**
- **5 lenght options as:** 150mm, 300mm, 600mm, 900mm, 1000mm and 1200mm


- Bends:



Accessories



RCC - Right corner connector



TCC - "T" corner connector



MIC - Middle connector

Features:

- Super slim design with 8mm height.
- High CRI 92 with 70 lm/w efficacy.
- Seamless continuous run without dark spots.
- Dot-free uniform light distribution with frosted lens.
- Plug and play system for speedy installation.
- Continuous run of 6 metres from single power supply.
- Remote 24V DC driver for ease of installation and maintenance.
- Cost effective, easy to install with numerous accessories.
- Life: 50,000 hours L90/B10.