

## Vertigo



### Product information

Source Type	LED Array
Corrected Colour Temperature	Specify 3000K or 4000K
Control Gear	Electronic Driver
IP	IP20
CRI	Specify 80 or 90
Beam angle	24°



This sleek recessed LED adjustable down light is available in three finishes satin white, matte black or black and white powder coated. The low-profile heat sink and the trim is constructed with high grade aluminum to extract heat out of the LED chip.

The faceted PC lens provide a low glare illumination. The Vertigo is designed with minimal trim width for stealth mode. This fitting is available in CRI80 standard or CRI90 on request. The high-quality COB LED Chip is 3- Step Mac-Adam Ellipse.

Non-dimmable ECG standard, Phase Dim/DALI is optional.

50,000-hour 5 year warranty

### Specification of the product

Power	7W	10W	15W	20W	25W
CRI	CRI80	CRI80	CRI80	CRI80	CRI80
Beam Angle	24°	24°	24°	24°	24°
Height	75mm	90mm	90mm	100mm	100mm
Cut out Ø	75mm	95mm	95mm	120mm	120mm
Luminous flux 3000K	546lm	780lm	1170lm	1560lm	1950lm
Luminous flux 4000K	616lm	881lm	1322lm	1762lm	2203lm
CCT	3000K	3000K	3000K	3000K	3000K
<b>Part No:</b>	<b>Vertigo7-23-CW-82</b>	<b>Vertigo10-23-CW-83</b>	<b>Vertigo15-23-CW-83</b>	<b>Vertigo20-23-CW-84</b>	<b>Vertigo25-23-CW-85</b>
CCT	4000K	4000K	4000K	4000K	4000K
<b>Part No:</b>	<b>Vertigo7-24-CW-82</b>	<b>Vertigo10-24-CW-83</b>	<b>Vertigo15-24-CW-83</b>	<b>Vertigo20-24-CW-84</b>	<b>Vertigo25-24-CW-85</b>