

## Nova Flex T IP67



### Product information



Corrected Colour Temperature	Specify 3000K or 4000K
Control gear	Electronic Driver
IP	IP67 Fitting
Power	10W & 16W
Dimensions of the flex	16mmx18mm

The Nova Flex S is a IP67 rated dot free high output architectural lighting solution. This LED fitting is only flexible in the vertical plain, this fitting has a flat diffuser. This product is more commonly used for the indoor or outdoor architectural lighting. This fitting can be mold in to curves and bends, minimum bend radius is 40mm.

Cut Length 85mm (markings are provided)

Flexible silicon material housing can be cut and bendable, Installs easily into linear aluminum "U" channel and/or mini-channel clips.

Non-dimmable ECG standard, Phase Dim/DALI is optional.

50,000-hour 5 year warranty

### Specification of the product

Power	10W/m	10W/m	16W/m	16W/m
CRI	CRI80	CRI80	CRI80	CRI80
luminous flux	520lm	560lm	944lm	982lm
CCT	3000K	4000K	3000K	4000K
<b>Part No:</b>	<b>Nova10-63-CW-86</b>	<b>Nova10-64-CW-86</b>	<b>Nova16-63-CW-86</b>	<b>Nova16-64-CW-86</b>
RGBW				
<b>Part No:</b>	<b>Nova10-63-CW-RBW6</b>			